



DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

№ 071

1. Unique identification code of the product-type:

HYDROZOL® BK (SV-BO)

EN 544:2011

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

production date on the package

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

bitumen shingles from APP modified bitumen reinforced with fiberglass, resistant to extreme weather conditions, used for long-lasting protection of water leakage in roofs with slope between 12° and 90°

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MARISAN & KOLEV JSC

Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment compliance system: 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified Party for certification of factory production control - INDEPENDENT CONSTRUCTION LABORATORY 'INFRASTRUCTURE' LTD with Identity number NB 2069 of the European Commission conducted type testing under system 3 and issued certificate of factory production control № 2069-CPD-0117/ 2008 and performs constant surveillance of the factory production control.





8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Not applicable

9. Declaration of performance:

Essential characteristics	Performance	Harmonized technical Specification
Reaction to fire	class E	EN 13501-1
Tensile strength - Longitudinally - transversely	≥ 600 N/50 mm ≥ 400 N/50 mm	EN 544:2011
Nail shank tear resistance - longitudinal - transversal	≥ 100 N ≥ 100 N	EN 544:2011
Flow resistance at elevated temperature	≥ 90 °C	EN 544:2011
Creep resistance at elevated temperature	≤ 2 mm	EN 544:2011

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV JSC.

Signed for and on behalf of the manufacturer:

Ruse
28.01.2015

General Manager:
/St. Kolev/

