

DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

№ 099

1. Unique identification code of the product-type:

HYDROZOL[®] HBM PRO (SBS-SVP)

EN 13 969 +A1:2006; EN 13 707 +A2:2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

production date on the package

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

hydro insulation membrane from SBS-Premium modified bitumen covered with mineral slate and reinforced with fiberglass, extreme elasticity, dimensional stability in wide operating temperature range : from -25⁰C to +100⁰C

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

MARISAN & KOLEV Ltd

Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Assessment compliance system: 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified Party for the assessment of compliance of construction products - Institute Of Testing and Certification – Czech Republic with Identity number NB 1023 of the European Commission conducted type testing under system 2+ and issued Type testing report № 753501076/ 2014.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued : **Not applicable**

9. Declaration of performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class F	EN 13501 – 5 EN 1187
Tensile strength - longitudinally - transversal	(500 ±100) N/50 mm (300 ±100) N/50 mm	EN 12311 - 1
Resistance to impact	h≥500 mm	EN 12691 (method A)
Resistance to static loading	h≥5 kg	EN 12730 (method A)
Elongation - longitudinal - transversal	[(3-4)±2] % [(3-4)±2] %	EN 12311 - 1
Nail shank tear resistance - longitudinal transversal	(100 ±50) N (100 ±50) N	EN 12310 - 1
Dimensional stability	< 0,6 %	EN 1107 - 1
Cold flexibility	< -25 ⁰ C	EN 1109
Flow resistance at elevated temperature	≥ +100 ⁰ C	EN 1110
Adhesion of granules	(15±15) %	EN 12039
Water tightness	300 kPa	EN 1928
Water vapour transmission properties	μ= 20000	EN 1931

Properties after artificial aging	-	EN 1296
Properties after artificial aging caused by elevated temperature		
<ul style="list-style-type: none"> - Flow resistance at elevated temperature 2h – upper face and lower face - Cold flexibility 	$(+100 \pm 5)^{\circ}\text{C}$ $(-25 \pm 5)^{\circ}\text{C}$	EN 1110 EN 1109

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV Ltd.

Signed for and on behalf of the manufacturer:

Ruse
28.03.2015

General Manager:
/St. Kolev/

