

DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

№ 158

1. Unique identification code of the product-type:

HYDROSTOP SINGLE-COMPONENT CEMENT-BASED HYDRO INSULATION EN 14891

2. Type, batch or serial number or any other element allowing identification of the construction product (as required to Article 11 (4)):

production date on the packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**cement-based waterproofing coating
for long-term protection against moisture
of non-deformable mineral surfaces and construction elements**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer (as required pursuant to Article 11 (5)):

**Made in EU for MARISAN & KOLEV AD
Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.**

5. (Where applicable) Name and contact address of the authorized representative (whose mandate covers the tasks specified in Article 12 (2)):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product (as set out in Annex V):

Assessment compliance system: 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Construction Materials Testing Laboratory by a Notified Party for the assessment of compliance of construction products – The Research Institute of Building Materials – NIISM EOOD with Identification number NB 1950 of the European Commission performed a type testing under system 3 and issued Test Report № ОТП-428/901/04.10.2018; № 901/04.10.2018 and № 901-1/04.10.2018.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable**

9. Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Grip strength after payback at normal conditions	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2017
Grip strength after water immersion	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2017
Grip strength after thermal treatment at 70°C	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2017
Grip strength after freeze/thaw cycles	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2017
Ability to bonding cracks: - under standard conditions ($23 \pm 2^\circ\text{C}$) - at 0°C	$\geq 0,75 \text{ mm}$	EN 14891:2017
Waterproofing	Sustains pressure 150 kPa	EN 14891:2017

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV AD.

Signed for and on behalf of the manufacturer by:

Ruse
18.01.2019

Executive Director:
/St. Kolev/

