

DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

№ 029

1. Unique identification code of the product-type:

**TERAFLEX[®] GYPSUM FILLER
EN 13279-1, class B4/20/2**

2. Type, batch or serial number or any other element allowing identification of the construction product (as required to Article 11 (4)):

production date on the packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**for plastering of walls and ceilings indoors,
producing smooth surfaces with extreme whiteness,
for layer thickness up to 10 mm**

4. (Name, registered trade name or registered trade mark and contact address of the manufacturer (as required pursuant to Article 11 (5)):

**MARISAN & KOLEV AD
Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.**

5. (Where applicable) Name and contact address of the authorized representative (whose mandate covers the tasks specified in Article 12 (2)):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product (as set out in Annex V):

Assessment compliance system: 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Construction Materials Testing Laboratory by a Notified Party for the assessment of compliance of construction products – The Research Institute of Building Materials – NIISM EOOD with Identification number NB 1950 of the European Commission performed a type testing under system 3 and issued Initial Type Testing Report №450/27.05.2011.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable**

9. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 (Euro class)	Declaration by the manufacturer, according to a decision of the EC
Content of gypsum binder (as CaSO ₄)	≥ 50%	EN 13279-1:2008
Initial setting time	≥ 20 min	EN 13279-1:2008
Tensile strength when bending	≥ 1 N/mm ²	EN 13279-1:2008
Compressive strength	≥ 2 N/mm ²	EN 13279-1:2008
Adhesion strength when tension	≥ 0,1 N/mm ²	EN 13279-1:2008

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV AD

Signed for and on behalf of the manufacturer by:

Ruse
15.03.2016

Executive Director:
/St. Kolev/

