

## DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

**№ 017**

1. Unique identification code of the product-type:

### **TERMOFLEX® ADHESIVE AND REINFORCING MORTAR FOR MINERAL WOOL**

**EN 13500, EN 12004, EN 998-1, class CSIV W1**

2. Type, batch or serial number or any other element allowing identification of the construction product (as required to Article 11 (4)):

**production date on the packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**adhesive mortar reinforced with fibers  
for bonding and plastering mineral wool boards  
for thermo-insulation of buildings**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer (as required pursuant to Article 11 (5)):

**MARISAN & KOLEV AD**

**Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.**

5. (Where applicable) Name and contact address of the authorized representative (whose mandate covers the tasks specified in Article 12 (2)):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product (as set out in Annex V):

**Assessment compliance system: 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**Construction Materials Testing Laboratory by a Notified Party for the assessment of compliance of construction products – The Research Institute of Building Materials – NIISM EOOD with Identification number NB 1950 of the European Commission performed a type testing under system 3 and issued Initial Type Testing Report № 1126/15.12.2007.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable**

9. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Adhesion strength of the main coating on EPS board	$\geq 60$ kPa	EN 13500:2004
Adhesion strength of the adhesive composition on EPS board	$\geq 60$ kPa	EN 13500:2004
Compressive strength of the 28 <sup>th</sup> day	$\geq 6$ N/mm <sup>2</sup> (category CS IV)	EN 988-1:2016
Capillary water adsorption	$\leq 40$ kg/(m <sup>2</sup> .min <sup>0.5</sup> ) (category W1)	EN 988-1:2016
Reaction to fire	A1 (Euro class)	EN 13501-1:2007+A1:2009

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV AD

Signed for and on behalf of the manufacturer by:

Ruse  
17.07.2018

Executive Director:  
/St. Kolev/



