

DECLARATION OF PERFORMANCE

In accordance with annex III of Regulation (EU) № 305/2011

№ 001

1. Unique identification code of the product-type:

TERAFLEX® CLASSIC

ADHESIVE FOR POROUS CERAMICS

EN 12004, class C1T

2. Type, batch or serial number or any other element allowing identification of the construction product (as required to Article 11 (4)):

production date on the packaging

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**adhesive for application of non-loaded porous ceramic linings,
terracotta and faience indoors**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer (as required pursuant to Article 11 (5)):

MARISAN & KOLEV AD

Ruse - 7009, East Industrial Zone, 15 Kalna Dere Str.

5. (Where applicable) Name and contact address of the authorized representative (whose mandate covers the tasks specified in Article 12 (2)):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product (as set out in Annex V):

Assessment compliance system: 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Construction Materials Testing Laboratory by a Notified Party for the assessment of compliance of construction products – The Research Institute of Building Materials – NIISM EOOD with Identification number NB 1950 of the European Commission performed a type testing under system 3 and issued Initial Type Testing Report № 10-17/01.10.2010.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable**

9. Declared performance:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	A1 (Euro class)	EN 13501-1:2007+A1:2009
Initial adhesion strength when tension	$\geq 0,5 \text{ N/mm}^2$	EN 12004-1:2017
Adhesion strength when tension after water immersion	$\geq 0,5 \text{ N/mm}^2$	EN 12004-1:2017
Adhesion strength when tension after heat ageing	$\geq 0,5 \text{ N/mm}^2$	EN 12004-1:2017
Adhesion strength when tension after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	EN 12004-1:2017
Open time: adhesion strength when tension	$\geq 0,5 \text{ N/mm}^2$ after not less than 20 min	EN 12004-1:2017

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:
Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4: MARISAN & KOLEV AD

Signed for and on behalf of the manufacturer by:

Ruse
10.07.2018

Executive Director
/St. Kolev/

